

## Open Body Turnbuckles Jaw - Jaw



### Product information

**General:**

- Generally to ASTM F 1145-92
- Standard hot dip galvanized.
- Factory supplied with lock nuts.
- Proof load 2.5 x WLL.
- Straight or in-line pull only.
- Drop forged high tensile steel.
- MBL equals or over 5x WLL

Part code	WLL ton	Thread mm	Thread Inch	Take up mm	L min. mm mm	L max. mm mm	A mm	Pmm mm	U mm mm	Wmm mm	Weight kg
11.51400250411	0.23	6.35	1/4	102	175	277	121	6	15	11	0.16
11.51400310411	0.36	7.94	5/16	114	212	314	138	6	22	13	0.24
11.51400330611	0.54	9.53	3/8	152	258	410	181	8	22	14	0.37
11.51400500611	1	12.7	1/2	152	292	470	190	10	27	16	0.71
11.51400500911	1	12.7	1/2	229	368	622	266	10	27	16	0.79
11.51400501211	1	12.7	1/2	305	445	775	343	10	27	15	1.09
11.51400620611	1.59	15.9	5/8	152	325	509	200	13	33	20	1.23
11.51400620911	1.59	15.9	5/8	229	401	662	276	13	33	20	1.56

11.51400621211	1.59	15.9	5/8	305	478	814	353	13	33	20	1.77
11.51400750611	2.36	19.1	3/4	152	356	546	210	16	38	24	1.86
11.51400750911	2.36	19.1	3/4	229	432	699	286	16	38	24	2.48
11.51400751211	2.36	19.1	3/4	305	508	851	362	16	38	24	2.98
11.51400751811	2.36	19.1	3/4	457	660	1,156	514	16	38	24	3.64
11.51400871211	3.27	22.2	7/8	305	543	892	370	19	44	29	3.71
11.51400871811	3.27	22.2	7/8	457	695	1,197	523	19	44	29	4.89
11.51401000611	4.54	25.4	1	152	425	628	228	22	52	34	4.62
11.51401001211	4.54	25.4	1	305	577	933	380	22	52	34	5.53
11.51401001811	4.54	25.4	1	457	729	1,237	532	22	52	34	6.87
11.51401002411	4.54	25.4	1	610	882	1,542	685	22	52	34	8.2
11.51401251211	6.89	31.8	1-1/4	305	644	1,012	384	28	71	44	9.34
11.51401251811	6.89	31.8	1-1/4	457	796	1,317	537	28	71	44	11.2
11.51401252411	6.89	31.8	1-1/4	610	948	1,622	689	28	71	44	12.8
11.51401501211	9.71	38.1	1-1/2	305	673	1,073	400	35	71	52	13.9
11.51401501811	9.71	38.1	1-1/2	457	826	1,359	553	35	71	52	16.7
11.51401502411	9.71	38.1	1-1/2	610	978	1,664	705	35	71	52	18.9
11.51401751811	12.7	44.5	1-3/4	457	899	1,356	568	41	86	66	24.5
11.51401752411	12.7	44.5	1-3/4	610	1,051	1,661	721	41	86	66	28.7
11.51402002411	16.8	51	2	610	1,157	1,766	738	51	94	66	46.5
11.51402502411	27.2	63.5	2-1/2	610	1,244	1,854	789	57	113	76	75
11.51402752411	34	70	2-3/4	610	1,289	1,899	788	70	106	92	90

## Blueprint

