

Open Body Turnbuckles Oval Eye - Oval Eye

Product information




General:

- Standard hot dip galvanized.
- Factory supplied with lock nuts.
- Testing on request.
- Proof load 2.5 x WLL.
- Straight or in-line pull only.
- Drop forged high tensile steel.
- MBL equals or over 5x WLL

... [Read more](#)

Open Body Turnbuckles Oval Eye - Oval Eye

Blueprint



Open Body Turnbuckles Oval Eye - Oval Eye

Technical data

Part code	WLL ton	Thread mm	Thread Inch	Take up mm	L min. mm	L max. mm	A mm	J mm	K mm	L mm	Weight kg
11.51400250422	0.23	6.35	1/4	102	198	300	121	6	9	20	0.12
11.51400310422	0.36	7.94	5/16	114	230	344	138	8	11	24	0.2
11.51400330622	0.54	9.53	3/8	152	291	444	181	9	13	28	0.34
11.51400500622	1	12.7	1/2	152	332	510	191	11	18	37	0.7
11.51400500922	1	12.7	1/2	229	409	614	266	11	18	37	0.77
11.51400501222	1	12.7	1/2	305	485	815	343	11	18	37	0.97
11.51400620922	1.59	15.9	5/8	229	450	655	276	13	22	44	1.32
11.51400620622	1.59	15.9	5/8	152	373	557	200	13	22	44	1.49
11.51400621222	1.59	15.9	5/8	305	525	862	353	13	22	44	1.55
11.51400750622	2.36	19.1	3/4	152	416	607	210	16	25	53	1.72
11.51400750922	2.36	19.1	3/4	229	492	697	286	16	25	53	1.92
11.514.0751222	2.36	19.1	3/4	305	568	911	362	16	25	53	2.49
11.51400751822	2.36	19.1	3/4	457	721	1,216	514	16	25	53	3.26
11.51400871222	3.27	22.2	7/8	305	592	942	370	19	32	60	3.27
11.51400871822	3.27	22.2	7/8	457	745	1,246	523	19	32	60	4.51
11.51401000622	4.54	25.4	1	152	507	710	228	23	36	76	4.1
11.51401001222	4.54	25.4	1	305	660	1,015	380	23	36	76	5.22
11.51401001822	4.54	25.4	1	457	812	1,320	532	23	36	76	6.35
11.51401002422	4.54	25.4	1	610	964	1,625	685	23	36	76	7.82
11.51401251222	6.89	31.8	1-1/4	305	719	1,087	384	29	46	90	8.62
11.51401251822	6.89	31.8	1-1/4	457	871	1,392	537	29	46	90	10.4
11.51401252422	6.89	31.8	1-1/4	610	1,024	1,697	689	29	46	90	12.2
11.51401501222	9.71	38.1	1-1/2	305	775	1,156	400	32	54	103	12.5
11.51401501822	9.71	38.1	1-1/2	457	927	1,461	553	32	54	103	14.1
11.51401502422	9.71	38.1	1-1/2	610	1,080	1,765	705	32	54	103	17
11.51401751822	12.7	44.5	1-3/4	457	1,000	1,457	568	38	60	117	23.8
11.51401752422	12.7	44.5	1-3/4	610	1,153	1,762	721	38	60	117	26.3
11.51402002422	16.8	51	2	610	1,313	1,923	738	45	68	146	8.7
11.51402502422	27.2	63.5	2-1/2	610	1,387	1,997	789	51	79	165	65
11.51402752422	34	70	2-3/4	610	1,448	2,057	788	57	82	177	88