


Pad Eyes Type S

Product information



Weldable lifting eye, available with lifting capacities from 1 up to 150 ton.

- Pad eyes will be supplied including material certificates (S355J2G3, EN 10204 3.1).
- $T \geq 75\%$ of inside width of shackle.
- $H \leq 106\%$ of diameter of pin.
- Weld primer applied.

... [Read more](#)


Material: Steel S355J2G3

Finish: Weldable primer

Safety factor: 6:1

Pad Eyes Type S

Blueprint



Technical data

| Part code | Rope Ø range mm | WLL ton | Shackle size | L mm | A mm | øH mm | R mm | t mm | T mm | Weight kg |
|----------------|-----------------|---------|--------------|------|------|-------|------|------|------|-----------|
| 11.4453001000S | 9-10 | 1 | 3/8 | 76 | 32 | 11.5 | 26 | 14 | 14 | 0.3 |
| 11.4453001500S | 9-10 | 1.5 | 7/16 | 90 | 32 | 13.5 | 32 | 15 | 15 | 0.5 |
| 11.4453002000S | 12-13 | 2 | 1/2 | 100 | 38 | 17 | 35 | 18 | 18 | 0.7 |
| 11.4453003250S | 19 | 3.25 | 5/8 | 115 | 45 | 20 | 38 | 22 | 22 | 1.5 |
| 11.4453004750S | 19 | 4.75 | 3/4 | 140 | 51 | 23 | 45 | 25 | 25 | 2 |
| 11.4453006500S | 25-26 | 6.5 | 7/8 | 150 | 57 | 26 | 51 | 30 | 30 | 3 |
| 11.4453008500S | 25-26 | 8.5 | 1 | 180 | 64 | 29.5 | 64 | 35 | 35 | 5 |
| 11.4453009500S | 25-26 | 9.5 | 1 1/8 | 203 | 76 | 33.5 | 76 | 40 | 40 | 7.5 |
| 11.4453012000S | 32 | 12 | 1 1/4 | 216 | 83 | 37 | 83 | 45 | 45 | 10 |
| 11.4453013500S | 32 | 13.5 | 1 3/8 | 228 | 89 | 40 | 89 | 30 | 50 | 10 |
| 11.4453017000S | 35 | 17 | 1 1/2 | 280 | 140 | 44 | 102 | 40 | 50 | 18 |
| 11.4453025000S | 41-42 | 25 | 1 3/4 | 305 | 140 | 53 | 121 | 40 | 60 | 23 |
| 11.4453035000S | 51 | 35 | 2 | 356 | 153 | 60 | 133 | 50 | 70 | 35 |
| 11.4453055000S | 63-64 | 55 | 2 1/2 | 482 | 165 | 74 | 152 | 50 | 90 | 55 |
| 11.4453085000S | 76-77 | 85 | 3 | 559 | 203 | 87 | 178 | 60 | 110 | 90 |
| 11.4453120000S | 95-96 | 120 | 3 1/2 | 711 | 254 | 100 | 229 | 70 | 120 | 170 |
| 11.4453150000S | 102 | 150 | 4 | 813 | 280 | 114 | 254 | 80 | 150 | 250 |