

Lanyard Skysafe Pro Flex (I) Skylotec L-0566

Product information



ONE4ALL - The SKYSAFE PRO

Revolutionary, new, patented energy absorber with the large weight range from 50 - 140kg which always withstands a maximum impact of less than 6 kN at a maximum absorber length of 1.75m.

The final impact resistance of 22 kN, also in the absorber, before AND after a fall is exceptional as well. SKYSAFE PRO furthermore meets the most relevant international standards in one SINGLE product.

UNIQUE: The built-in, adjustable RESCUE LOOPS! As a result, rescuers need not set up a rescue system and hereby save precious time in a rescue!

Available in four versions with different carabiner combinations: I-web, Y-web, I-web tie-back, Y-web tie-back.

Can be hand washed to 40°C.

Carabiner on anchoring point side: FS 90 ALU

Carabiner on belt side: STAK TRI

[... Read more](#)

Material: Polyester, Aluminium

Marking: According to standard, CE-marked, Supplier symbol, product id, art no, serial no, production year, standards, max. load.

Temperature range: -35°C up to 45°C.

Standard: EN 354, EN 355

Lanyard Skysafe Pro Flex (I) Skylotec L-0566

Technical data

Part code	Max. number of persons	Length m	Type	Weight kg
19.04L-0566-1.8	1	1.75	Single (I)	1.18