



Eye Self Locking Green Pin® UXLO

Product information

The Green Pin® Self-Locking Hook E is a grade 10 eye self-locking hook. The self-locking hook locks automatically as soon as it is brought under tension. To release the load the user must manually unlock the hook, which prevents unintended release. This hook brings a full safety for lifting as the latch cannot be removed. The eye of the hook can be connected to grade 10 chain with a connecting link, to a webbing with a web sling connector or to a wire rope with a thimble. The flat on the eye enables the assembly with an omega link or on a thimble. The Green Pin® Self-Locking Hook E is available in a range to suit 6 mm up to 20 mm grade 10 chain.

Certification on request: 2.1, 2.2, 3.1, MTCa, MPIb, DGUV

Material: Alloy steel, quenched and tempered

Temperature range: -40°C up to +200°C

Finish: Painted blue

Safety factor: 4:1

Grade: 10

| Part code | WLL ton | For chain Ø mm | For chain Ø inch | a mm | b mm mm | c mm | dmm mm | e mm mm | f mm mm | g mm mm | h mm mm | i mm mm | j mm mm | Weight kg |
|------------|---------|----------------|------------------|------|---------|------|--------|---------|---------|---------|---------|---------|---------|-----------|
| 11.15UXLO0 | 1.4 | 6 | 7/32 | 111 | 24 | 32 | 16 | 26 | 47 | 77 | 147 | 11 | 7 | 0.51 |
| 11.15UXLO1 | 2.6 | 8 | 5/16 | 134 | 29 | 43 | 23 | 29 | 57 | 92 | 176 | 14 | 7 | 0.91 |
| 11.15UXLO2 | 4 | 10 | 3/8 | 168 | 35 | 47 | 32 | 35 | 69 | 111 | 219 | 17 | 10 | 1.79 |
| 11.15UXLO3 | 6.8 | 13 | 1/2 | 199 | 46 | 61 | 37 | 45 | 87 | 142 | 264 | 20 | 13 | 3.36 |
| 11.15UXLO4 | 10.3 | 16 | 5/8 | 247 | 59 | 74 | 43 | 56 | 111 | 185 | 328 | 26 | 16 | 7 |

Blueprint

