



## Clevis Self Locking Hook UXLC, Green Pin®

### Product information

The self-locking hook locks automatically as soon as it is brought under tension. To release the load the user must manually unlock the hook, which prevents unintended release. This hook brings a full safety for lifting as the latch cannot be removed. The clevis design enables a direct connection to grade 10 chain. The Green Pin® Self-Locking Hook CL is available in a range to suit 6 mm up to 20 mm grade 10 chain.

**Certification:** at no extra charge this product can be supplied with a works certificate, a 3.1 material certificate and/or EC Declaration of Conformity

**Material:** alloy steel, quenched and tempered

**Temperature range:** -40°C up to +200°C

**Finish:** painted blue

**Safety factor:** 4:1

**Grade:** 10

Part code	Chain diameter mm	WLL ton	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	Weight kg
11.15GPUXLC0	6	1.4	92	7	32	16	26	28	77	131	8	0.49
11.15GPUXLC1	8	2.6	116	9	43	23	29	32	92	161	10	0.91
11.15GPUXLC2	10	4	143	12	47	32	35	42	111	200	13	1.77
11.15GPUXLC3	13	6.8	167	15	61	37	45	54	142	242	16	3.33

## Blueprint

