

## Clevis Self Locking Hook Green Pin® UXLC

---

### Product information



The self-locking hook locks automatically as soon as it is brought under tension. To release the load the user must manually unlock the hook, which prevents unintended release. This hook brings a full safety for lifting as the latch cannot be removed. The clevis design enables a direct connection to grade 10 chain. The Green Pin® Self-Locking Hook CL is available in a range to suit 6 mm up to 20 mm grade 10 chain.

Certification on request: 2.1, 2.2, 3.1, MTCa, MPIb

... [Read more](#)

---

**Material:** Alloy steel, quenched and tempered

**Temperature range:** -40°C up to +200°C


**Finish:** Painted blue

**Safety factor:** 4:1

**Grade:** 10

## Clevis Self Locking Hook Green Pin® UXLC

### Blueprint



### Technical data

Part code	Chain diameter mm	WLL ton	a mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	g mm mm	h mm mm	i mm mm	Weight kg
11.15GPUXLC0	6	1.4	92	7	32	16	26	28	77	131	8	0.49
11.15GPUXLC1	8	2.6	116	9	43	23	29	32	92	161	10	0.91
11.15GPUXLC2	10	4	143	12	47	32	35	42	111	200	13	1.77
11.15GPUXLC3	13	6.8	167	15	61	37	45	54	142	242	16	3.33