



Swivel Self Locking Hook Green Pin® UXLE

Product information

The Green Pin® Self-Locking Hook SE is a grade 10 swivel self-locking hook with eye. The self-locking hook locks automatically as soon as it is brought under tension. To release the load the user must manually unlock the hook, which prevents unintended release. This hook brings a full safety for lifting as the latch cannot be removed. The large eye, designed with a flat enables an easy assembly on anti-rotating wire rope slings (with an omega link or with thimbles). These hooks are fitted with a needle roller thrust bearing. This enables smooth, easy rotation under load. The eye of the hook can be connected to grade 8 chain with a connecting link or to a webbing with a web sling connector. The Green Pin® Self-Locking Hook SE is available in a range to suit 6 mm up to 20 mm grade 10 chain.

Certification on request: 2.1, 2.2, 3.1, MTCa, MPIb, DGUV

Material: Alloy steel, quenched and tempered

Temperature range: -40°C up to +200°C

Finish: Painted blue

Note: Equipped with needle roller thrust bearing to enable rotation under load

Safety factor: 4:1

Grade: 10

Part code	WLL ton	For chain Ø mm	For chain Ø inch	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	Weight kg
11.15UXLE0	1.4	6	7/32	122	32	32	32	16	26	77	192	12	6	0.78
11.15UXLE1	2.6	8	5/16	148	39	37	37	23	29	92	231	14	8	1.39
11.15UXLE2	4	10	3/8	183	46	48	47	32	35	111	282	16	11	2.56
11.15UXLE3	6.8	13	1/2	214	57	58	61	37	45	142	336	21	14	4.56
11.15UXLE4	10.3	16	5/8	269	65	73	74	39	56	185	416	24	17	9.37

Blueprint

