



Omega Link UCO, Green Pin®

Product information

The Green Pin® Omega Link is a grade 10 omega link. The omega link is used to make an easy and safe connection between the chain and any other components. The Green Pin® Omega Link is available in a range to suit 6 mm up to 16 mm grade 10 chain.

Certification: at no extra charge this product can be supplied with a works certificate, a 3.1 material certificate and/or EC Declaration of Conformity

Material: alloy steel, quenched and tempered

Temperature range: -40°C up to +200°C

Finish: painted blue

Safety factor: 4:1

Grade: 10

| Part Code | WLL ton | For chain ø mm | a mm | b mm | c mm | d mm | e mm | f mm | g mm | h mm | i mm | j mm | Weight kg |
|------------|------------|-------------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--------------|
| 11.06UCO6 | 1.4 | 6 | 14 | 8 | 7 | 25 | 20 | 53 | 13 | 41 | 28 | 6 | 0.07 |
| 11.06UCO8 | 2.6 | 8 | 21 | 10 | 9 | 34 | 24 | 72 | 16 | 58 | 32 | 9 | 0.18 |
| 11.06UCO10 | 4 | 10 | 21 | 13 | 12 | 40 | 31 | 84 | 19 | 67 | 42 | 11 | 0.28 |
| 11.06UCO13 | 6.8 | 13 | 28 | 16 | 15 | 51 | 40 | 109 | 23 | 90 | 54 | 14 | 0.64 |
| 11.06UCO16 | 10.3 | 16 | 35 | 20 | 19 | 64 | 48 | 135 | 27 | 110 | 68 | 17 | 1.21 |

Blueprint

