

## Connecting Link UMJ, Green Pin®



### Product information

This connecting link provide fast, easy assembly by using just a hammer. It is designed to connect eye and eye swivel hooks and master links to grade 10 chains all together. The spring bush ensures that the pin stay secured in place within the two halves of the connecting link. The Green Pin® Connecting Link is available in a range to suit 6 mm up to 20 mm grade 10 chain.

Certification on request: 2.1, 2.2, 3.1, MTCa, MPIb, DGUV

**Material:** alloy steel, quenched and tempered

**Temperature range:** -40°C up to +200°C

**Finish:** painted blue

**Safety factor:** 4:1

**Grade:** 10

Part code	WLL ton	For chain Ø mm	a mm	b mm mm	c mm	dmm mm	e mm mm	f mm mm	g mm mm	Weight kg
11.06GPUMJ6	1.4	6	8	42	11	20	52	11	15	0.09
11.06GPUMJ8	2.6	8	9	54	14	20	55	16	19	0.18
11.06GPUMJ10	4	10	12	66	18	23	64	18	25	0.31
11.06GPUMJ13	6.8	13	16	83	21	32	85	24	29	0.68
11.06GPUMJ16	10.3	16	19	103	25	40	105	28	36	1.27

# Blueprint

