



## Shortening Clutch UGC, Green Pin®

### Product information

The Green Pin® Shortening Clutch is a grade 10 shortening clutch. The shortening clutch is an essential part of chain slings, used to shorten the lengths of the chain legs and prevent instability of the load. The clutch compared to the shortening hook makes a straight pull possible. The Green Pin® Shortening Clutch is available in a range to suit 6 mm up to 20 mm grade 10 chain.

**Certification:** at no extra charge this product can be supplied with a works certificate, a 3.1 material certificate and/or EC Declaration of Conformity

**Material:** alloy steel, quenched and tempered

**Temperature range:** -40°C up to +200°C

**Finish:** painted blue

**Safety factor:** 4:1

**Grade:** 10

Part code	WLL ton	For chain Ø mm	For chain Ø inch	a mm	b mm	c mm	d mm	e mm	f mm	Weight kg
11.21UGC6	1.4	6	7/32	51	23	75	42	7	8	0.23
11.21UGC8	2.6	8	5/16	67	30	94	50	9	10	0.45
11.21UGC10	4	10	3/8	79	38	116	63	12	13	0.9
11.21UGC13	6.8	13	1/2	103	49	149	79	15	16	1.8
11.21UGC16	10.3	16	5/8	128	60	184	99	19	20	3.1

## Blueprint

