



Dee Shackle with Screw Pin Green Pin® MDVI, Stainless Steel

Product information

SS

The Green Pin® Stainless Steel Dee Shackle is a grade 5 dee shackle with a screw collar pin. The screw pin enables quick (dis)assembly which makes the shackle perfect for rigging activities in which assembly and disassembly occur relatively frequently. The Green Pin® Stainless Steel Dee Shackle can be used for both one-leg and multi-leg systems. The shackle is available in a range with a working load limit from 0.4 up to 6 ton.

Certification on request: 2.1, 2.2, 3.1

Material: AISI 316

Marking: CE-marked

Temperature range: -40°C up to +200°C

Finish: Polished.

Note: WLL

Safety factor: 5:1

Grade: 5

Code	WLL ton	Size	a mm	b mm	c mm	d mm	e mm	f mm	Weight kg
MDV0.4I	0.4	52	8	8	16	16	32	52	0.06
MDV0.6I	0.6	64	10	10	19	20	40	64	0.11
MDV0.9I	0.9	78	12	12	24	25	48	78	0.19
MDV1.5I	1.5	90	13	16	31	24	52	90	0.3
MDV2.5I	2.5	110	16	20	38	28	64	110	0.57
MDV3I	3	124	19	22	44	32	72	124	0.9
MDV4I	4	134	22	25	50	37	74	134	1.33
MDV6I	6	162	25	30	57	40	94	162	1.98

Blueprint

