



Turnbuckle Eye - Eye G-6311, Green Pin®

Product information

Turnbuckles are used for rigging or tensioning wires, ropes, rods etc. They are designed for in-line rigging, tensioning or lashing.

Standard: Generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b.

Certification: A works certificate, proof load test certificate and/or EC Declaration of Conformity can be supplied upon request

Material: Drop forged high tensile steel SAE 1035 or 1045

Marking: CE-marked

Temperature range: -20°C up to +200°C

Finish: Hot dipped galvanized

Safety factor: 5:1

Part code	WLL ton	Thread	Take up inch	a "	b mm	c mm	d mm	e mm	f mm	g mm	h mm	Weight kg
11.51SSGPOO1006	0.54	3/8	6	3/8	292	428	183	10	13	29	49	0.48
11.51SSGPOO1206	1	1/2	6	1/2	325	455	193	12	18	36	58	0.81
11.51SSGPOO1209	1	1/2	9	1/2	400	608	270	12	18	36	57	1.07
11.51SSGPOO1212	1	1/2	12	1/2	476	760	346	12	18	36	57	1.29
11.51SSGPOO1606	1.59	5/8	6	5/8	380	503	203	14	21	45	79	1.33
11.51SSGPOO1609	1.59	5/8	9	5/8	455	656	280	14	21	45	78	1.61
11.51SSGPOO1612	1.59	5/8	12	5/8	531	808	356	14	21	45	78	1.96
11.51SSGPOO1906	2.36	3/4	6	3/4	413	532	214	17	26	54	89	2.03

11.51SSGPOO1909	2.36	3/4	9	3/4	490	685	291	17	26	54	89	2.47
11.51SSGPOO1912	2.36	3/4	12	3/4	564	837	367	17	26	54	88	2.9
11.51SSGPOO1918	2.36	3/4	18	3/4	718	1,143	519	17	26	54	89	3.94
11.51SSGPOO2212	3.27	7/8	12	7/8	604	870	377	20	32	61	101	4.31
11.51SSGPOO2218	3.27	7/8	18	7/8	756	1,174	529	20	32	61	101	5.51
11.51SSGPOO2506	4.54	1	6	1	498	604	234	24	37	76	118	4.35
11.51SSGPOO2512	4.54	1	12	1	649	909	387	24	37	76	117	5.75
11.51SSGPOO2518	4.54	1	18	1	801	1,215	539	24	37	76	117	7.27
11.51SSGPOO2524	4.54	1	24	1	952	1,518	692	24	37	76	116	7.52
11.51SSGPOO3212	6.9	1 1/4	12	1 1/4	712	985	385	29	47	91	145	9.28
11.51SSGPOO3218	6.9	1 1/4	18	1 1/4	862	1,287	537	29	47	91	144	11.1
11.51SSGPOO3224	6.9	1 1/4	24	1 1/4	1,015	1,592	690	29	47	91	144	12.1
11.51SSGPOO3812	9.71	1 1/2	12	1 1/2	756	1,023	401	32	55	106	156	14.2
11.51SSGPOO3818	9.71	1 1/2	18	1 1/2	916	1,335	553	32	55	106	160	15.8
11.51SSGPOO3824	9.71	1 1/2	24	1 1/2	1,065	1,636	706	32	55	106	158	17.1
11.51SSGPOO4518	12.7	1 3/4	18	1 3/4	1,020	1,396	577	38	61	120	197	23.1
11.51SSGPOO4524	12.7	1 3/4	24	1 3/4	1,171	1,703	730	38	61	120	196	26.3
11.51SSGPOO5024	16.8	2	24	2	1,264	1,784	748	46	69	147	230	40.7
11.51SSGPOO6424	27.2	2 1/2	24	2 1/2	1,430	1,934	802	51	80	165	274	64
11.51SSGPOO6924	34	2 3/4	24	2 3/4	1,450	1,988	802	57	84	178	284	88

Blueprint

