



Master Link Assembly Green Pin® UMTS

Product information

The Green Pin[®] Master Link Assembly is a grade 10 master link assembly. This welded master link assembly is designed for 3 or 4 leg sling. The flat on the eye enables the assembly with an omega link or on a thimble. The Green Pin[®] Master Link Assembly is available in a range with a working load limit from 3.65 t. up to 41.6 t.

Certification: at no extra charge this product can be supplied with a works certificate and/or EC Declaration of Conformity

Material: alloy steel, quenched and tempered Temperature range: -40°C up to +200°C Finish: painted blue

Safety factor: 4:1 Grade: 10

| WLL ton | a mm | b mm | c mm | d mm | e mm | f mm | g mm | Weight kg |
|------------|---------|---------|---------|---------|---------|---------|---------|--------------|
| 3.65 | 18 | 135 | 75 | 16 | 120 | 70 | 7 | 1.97 |
| 6.8 | 22 | 170 | 90 | 18 | 135 | 75 | 9 | 3.3 |
| 11 | 28 | 209 | 120 | 20 | 150 | 82 | 11 | 5.4 |
| 17.7 | 36 | 270 | 145 | 25 | 190 | 103 | 13 | 11.2 |
| 21.2 | 38 | 250 | 150 | 30 | 235 | 125 | 17 | 15.1 |

Blueprint

