

## **Weld-On Transport Ring PAS**

## Product information

The Green Pin<sup>®</sup> Weld-On Transport Ring is a grade 8 weld-on transport ring. The base is forged from St 52-3 steel and the ring in 23MN. Welding must only be carried out by a qualified welder in accordance with DIN 8563 resp. 15429. The surfaces to be welded must be clean, without oil, grease or paint. Welding instructions are supplied with each delivery. The transport rings are delivered without springs.

Certification: at no extra charge this product can be supplied with a works certificate and/or EC Declaration of Conformity

Material: base: mild steel, ring: alloy steel, quenched and tempered

Marking: CE-marked

Temperature range: -40°C up to +200°C

Finish: painted white

Note: welding must be done in accordance with DIN 5817 resp. 15429, by a qualified welder according to EN 287-1

Safety factor: 4:1

Grade: 8

Code	Diameter mm	WLL ton	Size	A mm	B mm	C mm	D mm	e mm	f mm	Weight kg
PAS1	13	1.2	84	13	40	41	35	28	82	0.4
PAS3	18	3.2	101	18	45	47	42	33	98	0.77
PAS5	22	5.4	123	22	55	57	49	42	121	1.42
PAS8	26	8.2	145	26	70	67	64	50	143	2.5
PAS12	28	12.8	173	28	85	90	78	55	173	3.7
PAS15	34	15.5	191	34	99	93	90	63	190	5.67

## Blueprint

