Lifting Solutions Group
Axel Johnson International

ZHR chain block

Product information



General:
Heavy-duty hand chain block for loads from 500 up to 20,000 kg.

Technical characteristics:
Specification identical to those for the standard version of the VHR except for the following features :
- Overload limiter is standard equipment.
- 3 meters standrad lift. Hand chain is 0.5 meters less than lift chain.
- Four-bearing lifting mechanism.
- High strength grade 80 alloy steel load chain with corrosion-resistant galvanized (complies with standard EN 818, safety factor 4).
- Load chain Made in Europe.
- Galvanized hand chain made in Europe.
- Upper and lower alloy steel ISO hooks with safety latches.
- Weston-type load brakes.
- Offshore high-resistance RAL 7021 powder coating, 220 µ thick.
- Delivered with CE certificate, and hook and chain certificate.

Optional:
A wide range of options is available for this hand chain block. For example:
- ZHR with stainless steel load and hand chain.
- Chain bag.
- ZHR HPN with normal headroom.
- ZHR HPR with short headroom trolley.

... *Read more*

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

ZHR chain block

Technical data

Part code	Code	WLL ton	Lifting height m	Number of falls	Chain size mm	Pulling capacity kg	Weight kg
500100050300100	ZHR2	0.5	3	1	5 x 15	35	11
500100100300100	ZHR3	1	3	1	6 x 18	25	12.5
500100150300100	ZHR4	1.5	3	1	7,1 x 21	35	17.8
500100200300100	ZHR5	2	3	1	8 x 24	35	19.5
500100300300100	ZHR6	3	3	1	10 x 28	40	35
500100500300100	ZHR7	5	3	2	9 x 27	36	41.3
500100750300100	ZHR8	7.5	3	3	9 x 27	38	62
500101000300100	ZHR9	10	3	4	9 x 27	38	78.5
500101250300100	ZHR10	12.5	3	5	9 x 27	38,4	110
500101600300100	ZHR11	16	3	6	9 x 27	38,7	135
500102000300100	ZHR12	20	3	8	9 x 27	38,7	192

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved