

Wire Rope Lifting Sling WLS-176

Product information



Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²*

(*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm²)

Design: Master link in one end and self-locking safety hook in other end, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request..

... [Read more](#)

Wire Rope Lifting Sling WLS-176

Technical data

Part code	Diameter mm	WLL ton
WLS17603	3	0.12
WLS17604	4	0.21
WLS17605	5	0.32
WLS17606	6	0.47
WLS17608	8	0.82
WLS17609	9	1.04
WLS17610	10	1.28
WLS17611	11	1.55
WLS17612	12	1.84
WLS17613	13	2.17
WLS17614	14	2.51
WLS17616	16	3.3
WLS17618	18	4.1
WLS17620	20	5.1
WLS17622	22	6.2
WLS17624	24	7.38
WLS17626	26	8.66
WLS17628	28	10.04
WLS17632	32	13.12
WLS17636	36	16.59