MENNENS | Lifting Solutions Group
Axel Johnson International

# Anchor Point ABS-Lock Falz IV Standing Seam

**Product information**



Stainless steel anchor point ABS-Lock Falz IV Standing Seam clamped onto two metal seams - completely penetration-free.
Seam intervals: 300 - 450 mm/420 - 660 mm. This stainless steel anchorage point can be installed on standing seam roofs made of steel, copper, aluminium or titanium zinc without penetrating the roof surface.

**Force directions**: Lateral
**Substructure**: Seam roofs, profile roof
**Attachment**: Clamped, w/o roof penetration
**Application**: Profile roof, flat roofs

... *Read more*

**Material:** Stainless Steel
**Marking:** According to standard, CE-mark, Safety Instructions, Supplier symbol, Batch Nr., Standards, Max No of users, Serial Nr.
**Standard:** EN 795, CEN/TS/16415
**Note:** Incl. installation set.

**Mennens Nederland**
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Anchor Point ABS-Lock Falz IV Standing Seam

## Technical data

| Part code | Code | Max. number of persons |
|---|---|---|
| 8415PF4CU450 | PF-4-CU-450 | 3 |
| 8415PF4CU660 | PF-4-CU-660 | 3 |
| 8415PF4ST450 | PF-4-ST-450 | 3 |
| 8415PF4ST660 | PF-4-ST-660 | 3 |

**Mennens Nederland**
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved