MENNENS | Lifting Solutions Group
Axel Johnson International

Gantry Crane, Porta Gantry 500-5000kg

Product information



Lightweight Gantry Crane for lifting of goods and persons. The PORTAGANTRY has the ability to be moved under load. (Subject to detailed instruction and supervision by a competent person).

Goods WLL: 500kg up to 5000kg (depending on model)
Personnel WLL: Maximum combined personnel lifting capacity up to 2500kg (depending on model)
3-5 Person fall arrest: EN795:1997 certified – as part of an EN363 compliant system (500 & 1000 - 3 persons, 2000, 3000 & 5000 - 5 persons)
ATEX: All models suitable for use in ATEX Zone 2 explosive atmospheres
Lightweight & portable: With easy on-site assembly within manual handling guidelines:
- 4 portable parts assembled on just 4 bolts
- Simple ‘scissoring’ assembly in just 2-3 minutes

Ergonomic
- 360° swivel-locking castors as standard
- Simple, manual height & span adjustment
- Ultra-safe captive trolley
- Ergonomic design of profiles and handles

Stable: Bolted structure, lateral beam and leg bracing features
Configurations: Variety of standard configurations available, plus customisation for specific requirements and interchangeable components (subject to WLL rating)
Availability: 14 Days

... *Read more*

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Gantry Crane, Porta Gantry 500-5000kg

Technical data

Part code	WLL ton	Model	Max load kg	A-Frame weight	Max. number of persons	Standard Beam Length mm	Min height mm	Max height mm	overall span m	Weight kg
6015PGAS00500S2500A	0.5	A-frame S	250	32	3	2,500	1,595	2,345	1.58	89
6015PGAS00500S3000A	0.5	A-frame S	250	32	3	3,000	1,595	2,345	2.08	93
6015PGAS00500S3920A	0.5	A-frame S	250	32	3	3,920	1,595	2,345	3	100
6015PGAS00500S4570A	0.5	A-frame S	250	32	3	4,570	1,595	2,345	3.65	104
6015PGAS00500M2500A	0.5	A-frame M	250	42	3	2,500	2,091	2,841	1.58	109
6015PGAS00500S5500A	0.5	A-frame S	250	32	3	5,500	1,595	2,345	4.58	111
6015PGAS00500M3000A	0.5	A-frame M	250	42	3	3,000	2,091	2,841	2.08	113
6015PGAS00500S6000A	0.5	A-frame S	250	32	3	6,000	1,595	2,345	5.08	115
6015PGAS00500M3920A	0.5	A-frame M	250	42	3	3,920	2,091	2,841	3	120
6015PGAS00500M4570A	0.5	A-frame M	250	42	3	4,570	2,091	2,841	3.65	124
6015PGAS00500I3000A	0.5	A-frame I	250	50	3	3,000	2,178	3,178	2.08	129
6015PGAS00500M5500A	0.5	A-frame M	250	42	3	5,500	2,091	2,841	4.58	131
6015PGAS00500S8400A	0.5	A-frame S	250	32	3	8,400	1,595	2,345	7.48	132
6015PGAS00500M6000A	0.5	A-frame M	250	42	3	6,000	2,091	2,841	5.08	135
6015PGAS00500I3920A	0.5	A-frame I	250	50	3	3,920	2,178	3,178	3	136
6015PGAS00500S9000A	0.5	A-frame S	250	32	3	9,000	1,595	2,345	8.08	137
6015PGAS00500I4570A	0.5	A-frame I	250	50	3	4,570	2,178	3,178	3.65	141
6015PGAS00500T3000A	0.5	A-frame T	250	56	3	3,000	2,869	4,069	2.08	141
6015PGAS00500I5500A	0.5	A-frame I	250	50	3	5,500	2,178	3,178	4.58	148
6015PGAS00500T3920A	0.5	A-frame T	250	56	3	3,920	2,869	4,069	3	148
6015PGAS00500I6000A	0.5	A-frame I	250	50	3	6,000	2,178	3,178	5.08	151
6015PGAS00500M8400A	0.5	A-frame M	250	42	3	8,400	2,091	2,841	7.48	152
6015PGAS00500T4570A	0.5	A-frame T	250	56	3	4,570	2,869	4,069	3.65	153
6015PGAS00500M9000A	0.5	A-frame M	250	42	3	9,000	2,091	2,841	8.08	157
6015PGAS00500T5500A	0.5	A-frame T	250	56	3	5,500	2,869	4,069	4.58	159
6015PGAS00500T6000A	0.5	A-frame T	250	56	3	6,000	2,869	4,069	5.08	163
6015PGAS00500I8400A	0.5	A-frame I	250	50	3	8,400	2,178	3,178	7.48	169
6015PGAS00500I9000A	0.5	A-frame I	250	50	3	9,000	2,178	3,178	8.08	173
6015PGAS00500T8400A	0.5	A-frame T	250	56	3	8,400	2,869	4,069	7.48	180
6015PGAS00500T9000A	0.5	A-frame T	250	56	3	9,000	2,869	4,069	8.08	185
6015PGAS00500TC43920A	0.5	A-frame TC4	250	86	3	3,920	3,317	4,517	3	208

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Gantry Crane, Porta Gantry 500-5000kg

Technical data

Part code	WLL ton	Model	Max load kg	A-Frame weight	Max. number of persons	Standard Beam Length mm	Min height mm	Max height mm	overall span m	Weight kg
6015PGAS00500TC44570A	0.5	A-frame TC4	250	86	3	4,570	3,317	4,517	3.65	212
6015PGAS00500TC33920A	0.5	A-frame TC3	250	91	3	3,920	3,817	5,017	3	218
6015PGAS00500TC45500A	0.5	A-frame TC4	250	86	3	5,500	3,317	4,517	4.58	219
6015PGAS00500TC34570A	0.5	A-frame TC3	250	91	3	4,570	3,817	5,017	3.65	222
6015PGAS00500TC46000A	0.5	A-frame TC4	250	86	3	6,000	3,317	4,517	5.08	223
6015PGAS00500TC35500A	0.5	A-frame TC3	250	91	3	5,500	3,817	5,017	4.58	229
6015PGAS00500TC23920A	0.5	A-frame TC2	250	97	3	3,920	3,917	5,517	3	230
6015PGAS00500TC36000A	0.5	A-frame TC3	250	91	3	6,000	3,817	5,017	5.08	233
6015PGAS00500TC24570A	0.5	A-frame TC2	250	97	3	4,570	3,917	5,517	3.65	234
6015PGAS00500TC48400A	0.5	A-frame TC4	250	86	3	8,400	3,317	4,517	7.48	240
6015PGAS00500TC13920A	0.5	A-frame TC1	250	102	3	3,920	4,019	5,819	3	240
6015PGAS00500TC25500A	0.5	A-frame TC2	250	97	3	5,500	3,917	5,517	4.58	241
6015PGAS00500TC49000A	0.5	A-frame TC4	250	86	3	9,000	3,317	4,517	8.08	245
6015PGAS00500TC26000A	0.5	A-frame TC2	250	97	3	6,000	3,917	5,517	5.08	245
6015PGAS00500TC14570A	0.5	A-frame TC1	250	102	3	4,570	4,019	5,819	3.65	245
6015PGAS00500TC38400A	0.5	A-frame TC3	250	91	3	8,400	3,817	5,017	7.48	250
6015PGAS00500TC15500A	0.5	A-frame TC1	250	102	3	5,500	4,019	5,819	4.58	252
6015PGAS00500TC39000A	0.5	A-frame TC3	250	91	3	9,000	3,817	5,017	8.08	255
6015PGAS00500TC16000A	0.5	A-frame TC1	250	102	3	6,000	4,019	5,819	5.08	255
6015PGAS00500TC28400A	0.5	A-frame TC2	250	97	3	8,400	3,917	5,517	7.48	263
6015PGAS00500TC29000A	0.5	A-frame TC2	250	97	3	9,000	3,917	5,517	8.08	267
6015PGAS00500TC18400A	0.5	A-frame TC1	250	102	3	8,400	4,019	5,819	7.48	273
6015PGAS00500TC19000A	0.5	A-frame TC1	250	102	3	9,000	4,019	5,819	8.08	277
6015PGAS00500I2500A	0.5	A-frame I	250	50	3	2,500	2,178	3,178	1.58	-
6015PGAS00500T2500A	0.5	A-frame T	250	56	3	2,500	2,869	4,069	1.58	-
6015PGAS00500TC42500A	0.5	A-frame TC4	250	86	3	2,500	3,317	4,517	1.58	-
6015PGAS00500TC43000A	0.5	A-frame TC4	250	86	3	3,000	3,317	4,517	2.08	-
6015PGAS00500TC32500A	0.5	A-frame TC3	250	91	3	2,500	3,817	5,017	1.58	-
6015PGAS00500TC33000A	0.5	A-frame TC3	250	91	3	3,000	3,817	5,017	2.08	-
6015PGAS00500TC22500A	0.5	A-frame TC2	250	97	3	2,500	3,917	5,517	1.58	-

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Gantry Crane, Porta Gantry 500-5000kg

Technical data

Part code	WLL ton	Model	Max load kg	A-Frame weight	Max. number of persons	Standard Beam Length mm	Min height mm	Max height mm	overall span m	Weight kg
6015PGAS00500TC23000A	0.5	A-frame TC2	250	97	3	3,000	3,917	5,517	2.08	-
6015PGAS00500TC12500A	0.5	A-frame TC1	250	102	3	2,500	4,019	5,819	1.58	-
6015PGAS00500TC13000A	0.5	A-frame TC1	250	102	3	3,000	4,019	5,819	2.08	-
6015PGAS01000S2500A	1	A-frame S	500	32	3	2,500	1,605	2,355	1.58	89
6015PGAS01000S3000A	1	A-frame S	500	32	3	3,000	1,605	2,355	2.08	93
6015PGAS01000S3920A	1	A-frame S	500	32	3	3,920	1,605	2,355	3	100
6015PGAS01000S4570A	1	A-frame S	500	32	3	4,570	1,605	2,355	3.65	104
6015PGAS01000M2500A	1	A-frame M	500	42	3	2,500	2,101	2,851	1.58	109
6015PGAS01000S5500A	1	A-frame S	500	32	3	5,500	1,605	2,355	4.58	111
6015PGAS01000M3000A	1	A-frame M	500	42	3	3,000	2,101	2,851	2.08	113
6015PGAS01000S6000A	1	A-frame S	500	32	3	6,000	1,605	2,355	5.08	115
6015PGAS01000M3920A	1	A-frame M	500	42	3	3,920	2,101	2,851	3	120
6015PGAS01000S8400A	1	A-frame S	500	32	3	8,400	1,605	2,355	7.48	149
6015PGAS01000S9000A	1	A-frame S	500	32	3	9,000	1,605	2,355	8.08	155

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved