

Wire Rope Lifting Sling WLS-115

Product information



Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²*

(* \varnothing 3mm - \varnothing 7mm rope construction: 6x19M WSC 1960 N/mm²)

Design: Soft eye in one end and eyehook with safety latch in other end, mechanical aluminium spliced.

Load table at Technical Data -> [Show table](#)

Please specify the needed (working) length and eye length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

... [Read more](#)

Wire Rope Lifting Sling WLS-115

Technical data

Part code	Rope diameter	WLL ton
WLS11503	3	0.12
WLS11504	4	0.21
WLS11505	5	0.32
WLS11506	6	0.47
WLS11508	8	0.82
WLS11509	9	1.04
WLS11510	10	1.28
WLS11511	11	1.55
WLS11512	12	1.84
WLS11513	13	2.17
WLS11514	14	2.51
WLS11516	16	3.3
WLS11518	18	4.1
WLS11520	20	5.1
WLS11522	22	6.2
WLS11524	24	7.38
WLS11526	26	8.66
WLS11528	28	10.04
WLS11532	32	13.12
WLS11536	36	16.59
WLS11540	40	20.56
WLS11544	44	24.78
WLS11548	48	29.55
WLS11552	52	34.69