



## Wire Rope Lifting Sling WLS-116

### Product information

**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>\***

(\*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm<sup>2</sup>)

**Design:** Soft eye in one end and self-locking safety hook in other end, mechanical aluminium spliced.

Load table at Technical Data -> Show table

Please specify the needed (working) length and eye length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

<b>Part code</b>	<b>Diameter mm</b>	<b>WLL ton</b>
WLS11603	3	0.12
WLS11604	4	0.21
WLS11605	5	0.32
WLS11606	6	0.47
WLS11608	8	0.82
WLS11609	9	1.04
WLS11610	10	1.28
WLS11611	11	1.55
WLS11612	12	1.84
WLS11613	13	2.17
WLS11614	14	2.51
WLS11616	16	3.3
WLS11618	18	4.1
WLS11620	20	5.1
WLS11622	22	6.2
WLS11624	24	7.38
WLS11626	26	8.66
WLS11628	28	10.04
WLS11632	32	13.12
WLS11636	36	16.59

## Technical data