



## Wire Rope Lifting Sling WLS-164

### Product information

**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>\***

(\*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm<sup>2</sup>)

**Design:** Master link in one end and soft eye in other end, mechanical aluminium spliced.

Load table at Technical Data -> Show table

Please specify the needed (working) length and eye length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

Part code	Diameter mm	WLL ton
WLS16403	3	0.12
WLS16404	4	0.21
WLS16405	5	0.32
WLS16406	6	0.47
WLS16408	8	0.82
WLS16409	9	1.04
WLS16410	10	1.28
WLS16411	11	1.55

WLS16412	12	1.84
WLS16413	13	2.17
WLS16414	14	2.51
WLS16416	16	3.3
WLS16418	18	4.1
WLS16420	20	5.1
WLS16422	22	6.2
WLS16424	24	7.38
WLS16426	26	8.66
WLS16428	28	10.04
WLS16432	32	13.12
WLS16436	36	16.59
WLS16440	40	20.56
WLS16444	44	24.78
WLS16448	48	29.55
WLS16452	52	34.69

## Technical data