



Wire Rope Lifting Sling WLS-173

Product information

Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²*

(*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm²)

Design: Master link in one end and thimble in other end, mechanical aluminium spliced.

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

Part code	Diameter mm	WLL ton
WLS17303	3	0.12
WLS17304	4	0.21
WLS17305	5	0.32
WLS17306	6	0.47
WLS17308	8	0.82
WLS17309	9	1.04
WLS17310	10	1.28
WLS17311	11	1.55
WLS17312	12	1.84
WLS17313	13	2.17
WLS17314	14	2.51
WLS17316	16	3.3
WLS17318	18	4.1
WLS17320	20	5.1
WLS17322	22	6.2
WLS17324	24	7.38
WLS17326	26	8.66
WLS17328	28	10.04
WLS17332	32	13.12
WLS17336	36	16.59
WLS17340	40	20.56
WLS17344	44	24.78
WLS17348	48	29.55
WLS17352	52	34.69

Technical data