

## Wire Rope Lifting Sling WLS-180

---

### Product information



**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>\***

(\*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm<sup>2</sup>)

**Design:** Master link in both ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> [Show table](#)

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request..

... [Read more](#)

---

## Wire Rope Lifting Sling WLS-180

### Technical data

Part code	Diameter mm	WLL ton
WLS18003	3	0.12
WLS18004	4	0.21
WLS18005	5	0.32
WLS18006	6	0.47
WLS18008	8	0.82
WLS18009	9	1.04
WLS18010	10	1.28
WLS18011	11	1.55
WLS18012	12	1.84
WLS18013	13	2.17
WLS18014	14	2.51
WLS18016	16	3.3
WLS18018	18	4.1
WLS18020	20	5.1
WLS18022	22	6.2
WLS18024	24	7.38
WLS18026	26	8.66
WLS18028	28	10.04
WLS18032	32	13.12
WLS18036	36	16.59
WLS18040	40	20.56
WLS18044	44	24.78
WLS18048	48	29.55
WLS18052	52	34.69