



Wire Rope Lifting Sling WLS-264

Product information

Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²

Design: Master link in one end and soft eyes in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length and eye lengths with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

Part code	Diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
WLS26403	3	0.16	0.16	0.12
WLS26404	4	0.29	0.29	0.21
WLS26405	5	0.45	0.45	0.32
WLS26406	6	0.66	0.66	0.47
WLS26408	8	1.15	1.15	0.82
WLS26409	9	1.45	1.45	1.04
WLS26410	10	1.79	1.79	1.28
WLS26411	11	2.17	2.17	1.55

WLS26412	12	2.57	2.57	1.84
WLS26413	13	3.03	3.03	2.17
WLS26414	14	3.52	3.52	2.51
WLS26416	16	4.6	4.6	3.3
WLS26418	18	5.81	5.81	4.1
WLS26420	20	7.17	7.17	5.1
WLS26422	22	8.69	8.69	6.2
WLS26424	24	10.33	10.33	7.38
WLS26426	26	12.13	12.13	8.66
WLS26428	28	14.06	14.06	10.04
WLS26432	32	18.37	18.37	13.12
WLS26436	36	23.23	23.23	16.59
WLS26440	40	28.78	28.78	20.56
WLS26444	44	34.69	34.69	24.78
WLS26448	48	41.37	41.37	29.55
WLS26452	52	52.04	52.04	34.69

Technical data