



Wire Rope Lifting Sling WLS-276

Product information

Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²

Design: Master link in one end and selflocking eye-safetyhooks in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

Part code	Diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
WLS27603	3	0.16	0.16	0.12
WLS27604	4	0.29	0.29	0.21
WLS27605	5	0.45	0.45	0.32
WLS27606	6	0.66	0.66	0.47
WLS27608	8	1.15	1.15	0.82
WLS27609	9	1.45	1.45	1.04
WLS27610	10	1.79	1.79	1.28
WLS27611	11	2.17	2.17	1.55
WLS27612	12	2.57	2.57	1.84
WLS27613	13	3.03	3.03	2.17
WLS27614	14	3.52	3.52	2.51
WLS27616	16	4.6	4.6	3.3
WLS27618	18	5.81	5.81	4.1
WLS27620	20	7.17	7.17	5.1
WLS27622	22	8.69	8.69	6.2
WLS27624	24	10.33	10.33	7.38
WLS27626	26	12.13	12.13	8.66
WLS27628	28	14.06	14.06	10.04
WLS27632	32	18.37	18.37	13.12
WLS27636	36	23.23	23.23	16.59

Technical data