MENNENS | Lifting Solutions Group
Axel Johnson International

Wire Rope Lifting Sling WLS-273

Product information



Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm2
Design: Master link in one end and thimble in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

... *Read more*

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Wire Rope Lifting Sling WLS-273

Technical data

Part code	Diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
WLS27303	3	0.16	0.16	0.12
WLS27304	4	0.29	0.29	0.21
WLS27305	5	0.45	0.45	0.32
WLS27306	6	0.66	0.66	0.47
WLS27308	8	1.15	1.15	0.82
WLS27309	9	1.45	1.45	1.04
WLS27310	10	1.79	1.79	1.28
WLS27311	11	2.17	2.17	1.55
WLS27312	12	2.57	2.57	1.84
WLS27313	13	3.03	3.03	2.17
WLS27314	14	3.52	3.52	2.51
WLS27316	16	4.6	4.6	3.3
WLS27318	18	5.81	5.81	4.1
WLS27320	20	7.17	7.17	5.1
WLS27322	22	8.69	8.69	6.2
WLS27324	24	10.33	10.33	7.38
WLS27326	26	12.13	12.13	8.66
WLS27328	28	14.06	14.06	10.04
WLS27332	32	18.37	18.37	13.12
WLS27336	36	23.23	23.23	16.59
WLS27340	40	28.78	28.78	20.56
WLS27344	44	34.69	34.69	24.78
WLS27348	48	41.37	41.37	29.55
WLS27352	52	52.04	52.04	34.69

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved