

## Trec LH Mobile shelf ladder

### Product information



**General:** For easy rolling along the shelves: The solution is equipped with guide rails and self-locking sprung castors and can be customised to the desired height. In case of order, please provide the distance from the floor to the top edge of the rail.

#### Features and benefits:

- Both the top of the ladder and the self-locking sprung castors at the bottom lock the shelf ladder when weight is applied.
- When not in use, the ladder can be stowed vertically on the shelf to save space.

#### Available in 3 Types:

1. **Comfortstep Trec LH** (ladder width 380 mm)  
Screwed tread with padded front edge.  
Base length = vertical height of the guide rail  $\times$  0.404
2. **Saferstep Trec LH** (ladder width 420 mm)  
Edge-formed tread with ZARGES Safer Step Technology.  
Base length = vertical height of the guide rail  $\times$  0.364
3. **Stella Trec LH** (ladder width 490 mm)  
edge-formed wide rung.  
Base length = vertical height of the guide rail  $\times$  0.268

#### Accessories Optional (to be ordered separately):

**A1:** 99.XX40370 Aluminium alloy tube,  $\varnothing$  30 mm, 3000 mm long, anodised

**A2:** 99.XX41457 Aluminium alloy intermediate bracket.

**A3:** 99.XX41457 Aluminium alloy bracket with stop on the right

**A4:** 99.XX41457 Aluminium alloy bracket with stop on the left.

Rail systems: One intermediate bracket is required for every approx. 1.00 m of tubina. [... Read more](#)

**Material:** Aluminium

**Marking:** According to standard


**Finish:** anodised

**Standard:** EN 131 Cat. Professional

**Note:** Max. load 150 kg.

## Trec LH Mobile shelf ladder

### Blueprint



### Technical data

Part code	Type	number of treads	from/to maximum vertical hook-on height m	no. of rungs
99.XX0041412	1: Comfortstep Trec LH	6	1.84–2.08	-
99.XX0041413	1: Comfortstep Trec LH	7	2.09–2.33	-
99.XX0041414	1: Comfortstep Trec LH	8	2.34–2.58	-
99.XX0041415	1: Comfortstep Trec LH	9	2.59–2.83	-
99.XX0041416	1: Comfortstep Trec LH	10	2.84–3.08	-
99.XX1141356	2: Saferstep Trec LH	6	1.67–2.16	-
99.XX1141358	2: Saferstep Trec LH	8	2.17–2.67	-
99.XX1141360	2: Saferstep Trec LH	10	2.68–3.20	-
99.XX1141362	2: Saferstep Trec LH	12	3.21–3.72	-
99.XX1141364	2: Saferstep Trec LH	14	3.73–4.25	-
99.XX1141511	3: Stella Trec LH	-	1.73-2.26	6
99.XX1141512	3: Stella Trec LH	-	2.27-2.80	8
99.XX1141513	3: Stella Trec LH	-	2.81-3.34	10
99.XX1141514	3: Stella Trec LH	-	3.35-3.88	12
99.XX1141515	3: Stella Trec LH	-	3.89-4.42	14
99.XX0040370.	A1	-	-	-
99.XX0041457.	A2	-	-	-
99.XX0041458.	A3  mm	-	-	-
99.XX0041459.	A4  mm	-	-	-