



Skyline 3E Rope-operated ladder, 3-part

Product information

General: When you need access to great heights: Optimised transport dimensions, working heights of up to 16.35 m with convenient height adjustment.

Features and benefits:

- Two ropes so that centre and top sections can be adjusted separately.
- Rung-by-rung height adjustment in a grid of 280 mm.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- Locks securely thanks to automatic spring loaded pawls.
- The ladders with the part codes 99.XX40448 and 40449 are equipped with 2 light alloy supports for easy erection and stabilisation. (Not to be used as free-standing ladders!)
- Improved plastic guide.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.

Material: Aluminium

Marking: According to standard

Finish: Natural

Standard: EN 131 Cat. Professional

Note: Max. load 150 kg.

Part code	working height approx. m	stile height mm	number of rungs	ladder length, extended m	ladder length, retracted m	outside width of lower ladder mm	Width horizontal stabiliser bar m	Weight kg
99.XX40446	11.15	86 - 98	3 × 15	10.55	4.4	560	1.2	45
99.XX40447	13.1	86 - 98	3 × 18	12.55	5.25	560	1.2	53
99.XX40448	14.7	86 - 98	3 × 20	14.2	5.8	590	-	68
99.XX40449	16.35	86 - 98	3 × 22	15.9	6.4	590	-	74