



Multi-function ladder Skymaster X, 3-part

Product information

General: Convertible to take on challenging tasks with greater safety. Offers high functionality and flexibility and an excellent price/performance ratio.

Features and benefits:

- Can be used on steps/stairs (code. 41536-41540 up to 3x10 rungs).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for code. 41536-41540 up to 3x10 rungs.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.

Material: Aluminium

Marking: According to standard

Standard: EN 131 Cat. Professional

Note: Max load 150 kg.

| Part code | stile height mm | ladder length, retracted m | ladder length as 3-part ladder m | single length as 2-part single ladder and as stepladder with push-on part m | max. working height as 3-part single ladder approx. m | Horizontal stabiliser bar m | no. of rungs | Weight kg |
|--------------|-----------------------|----------------------------------|--|---|---|-----------------------------------|-----------------|--------------|
| 41536 | 68 | 1.9 | 4.1 | 3 | 5 | 0.8 | 3 x 6 | 13.8 |
| 41537 | 68 | 2.2 | 5 | 3.6 | 5.8 | 0.9 | 3 x 7 | 15 |
| 41538 | 73 | 2.45 | 5.8 | 4.1 | 6.65 | 1 | 3 x 8 | 17.5 |
| 41539 | 85 | 2.7 | 6.7 | 4.7 | 7.45 | 1.1 | 3 x 9 | 20 |
| 41540 | 85 | 3 | 6.9 | 4.95 | 7.7 | 1.1 | 3 x 10 | 23.3 |
| 41542 | 98 | 3.55 | 8.6 | 6.1 | 9.35 | 1.2 | 3 x 12 | 28.8 |
| 41544 | 98 | 4.15 | 9.7 | 6.95 | 10.4 | 1.2 | 3 x 14 | 36.4 |

Blueprint