



Work platform - Scaffolding Variomaster T

Product information

General: For quick use and safe standing: folds to compact size and is quickly set up.

Features and benefits:

- Large-area work platform 0.50 x 1.95 m or 0.60 x 2.50 m.
- Peripheral railing for maximum work safety.
- Simple height adjustment according to the self-locking push-up ladder principle, allowing you to reach different heights with only one work platform.
- Operation of height adjustment by one person.
- Easily collapsible for transport and storage.
- Highly mobile and able to pass through doors when erected and collapsed thanks to rollers (Order No. 53794).
- Extendable stabilisers with sturdy height-adjustable foot plates for stability and for levelling out on uneven ground.
- No ballast weights are required for indoor use.
- Two sizes with height adjustment from 1.25 m to 2.46 m or 1.81 m to 3.58 m platform height.
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.

Optional: Ballast weight for outdoor use to be ordered separately. 12 Pcs. required

Material: Aluminium

Note: max. load 300 kg.

Warning: For outdoor use, ballast weights are required. (12Pc) . Sold separately.

Part Code	working height approx. m	Platform height m	base area, stabiliser extended, L x W m	scaffolding height overall	base area without stabiliser L x W m	Weight kg
53794	4.5	1.25 - 2.46	1.90 x 2.30	2.31 - 3.52	0.80 x 2.30	92
53795	5.6	1.81 - 3.58	2.30 x 2.85	2.87 - 4.64	1.20 x 2.85	119