MENNENS | Lifting Solutions Group
Axel Johnson International

CREAXESS Mobile access steps with platform

Product information



Mobile access or work platforms with easy-going steps. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.

Features and benefits:

- Different angles of inclination: 45° for comfortable access, 60° for confined spaces.
- Serrated aluminium (R10) step and platform surfaces as standard. Steel gratings (R12) and perforated steel plates (R13) are also available for higher non-slip performance.
- Cantilever platform available for bridging obstacles.
- An antistatic version of the chassis is also available.
- Customised guardrail configuration on the platform, with optional swing door or pole barrier.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Individually adjustable platform lengths.
- Narrow chassis: the chassis width is reduced to a minimum through additional ballasting.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure suffic ... *Read more*

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

CREAXESS Mobile access steps with platform

Technical data

Part code	I'd like to have more information about this service
9098	CREAXESS - Platformtrap / Mobile acces step / Échelle plate-forme mobile

access steps with platform, mobile, with double sided handrail and peripheral platform railing - 45° inclination.											
Vertical height	**overall span**	**number of treads**	**tread width 600 mm**			**tread width 800 mm**			**tread width 1000 mm**		
mm			**chassis width in mm**	**order no.**		**chassis width in mm**	**order no.**		**chassis width in mm**	**order no.**	
1070	1620	5	1000	402	59764	1200	402	59784	1400	402	59804
1500	2050	7	1000	402	59766	1200	402	59786	1400	402	59806
1930	2480	9	1000	402	59768	1200	402	59788	1400	402	59808
2360	2910	11	1000	402	59770	1200	402	59790	1400	402	59810
2790	3340	13	1400	402	59772	1200	402	59792	1400	402	59812
3220	3770	15	1400	402	59774	1200	402	59794	1400	402	59814
3650	4200	17	1400	402	59776	1200	402	59796	1400	402	59816

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

CREAXESS Mobile access steps with platform

access steps with platform, mobile, with double sided handrail and peripheral platform railing - 60° inclination.											
Vertical height	overall span	number of treads	tread width 600 mm			tread width 800 mm			tread width 1000 mm		
mm			chassis width in mm	order no.		chassis width in mm	order no.		chassis width in mm	order no.	
1250	1342	5	1000	402	59704	1200	402	59724	1400	402	59744
1750	1631	7	1000	402	59706	1200	402	59726	1400	402	59746
2250	1919	9	1200	402	59708	1200	402	59728	1400	402	59748
2750	2208	11	1400	402	59710	1400	402	59730	1600	402	59750
3250	2497	13	1600	402	59712	1600	402	59732	1600	402	59752
3750	2785	15	1600	402	59714	1600	402	59734	1600	402	59754

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved