



## CREAXESS Mobile access steps with platform, Auto- or Ergo Stop

### Product information

Mobile access or work platforms with easy-going steps. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.

#### Features and benefits:

- Different angles of inclination: 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Steel gratings (R12) and perforated steel plates (R13) are also available for higher non-slip performance.
- Individually adjustable platform lengths.
- Platform steps instantly ready for use due to an innovative brake system.
- An antistatic version of the chassis is also available.
- ZARGES Ergo Stop - all four castors can be braked conveniently using the foot pedal on the flight of steps.
- Customised guardrail configuration on the platform, with optional swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

- Standard applied: DIN EN ISO 14 122.

I'd like to have more information about this service

CREAXESS Ergo Stop - Platformtrap / Mobile acces step / Échelle plate-forme mobile

Technical data

access steps with platform, mobile, with double-sided handrail and peripheral platform railing - 45° inclination.							
Vertical height	overall span	number of treads	chassis width	ZARGES auto stop* tread width 800 mm		ZARGES ergo stop** tread width 800 mm	
mm	mm		mm	order no.		order no.	
1070	2220	5	1000	402	59611	402	5965
1500	2650	7	1000	402	59613	402	5965
1930	3080	9	1000	402	59615	402	5965
2360	3510	11	1200	402	59617	402	5965
2790	3940	13	1400	402	59619	402	5965
3220	4370	15	1400	402	59621	402	5966
3650	4800	17	1400	402	59623	402	5966
access steps with platform, mobile, with double sided handrail and peripheral platform railing - 60° inclination.							
Vertical height	overall span	number of treads	chassis width	ZARGES auto stop* tread width 800 mm		ZARGES ergo stop ** tread width 800 mm	
mm	mm		mm	order no.		order no.	
1250	1942	5	1200	402	59631	402	5967
1750	2231	7	1200	402	59633	402	5967
2250	2519	9	1200	402	59635	402	5967
2750	2808	11	1400	402	59637	402	5967
3250	3097	13	1600	402	59639	402	5967

3750	3385	15	1600	402	59641	402	5968
------	------	----	------	-----	-------	-----	------

<b>optional</b>							
<b>designation</b>							
<b>order no.</b>							
41967	Aluminium storage tray						
41968	Large storage and retrieval tray						
43800000	Anchorage for ZARGES cases up to 800 mm.						