



DYNICE Warp Winch Ropes

Product information

Specialized high performance rope for extreme deep sea lowering and lifting and towing fishing trawls and it is an excellent choice as winch wire rope replacement.

DynIce Warp is proven to use on drum winches both in fishing and offshore and is very suitable for traction winches.

Design: 6 different layers to make the line with very high cross-sectional stability and axial stiffness. The rope is a heat set and stretched rope with plastic core to ensure firmness and roundness and a durable cover of Dyneema® overbraid is moulded on the main rope. The main strength member and the cover is braided ensuring that the rope is totally balanced and torque free and will not untwist at any load.

Note: The density is 0,96 and the rope is floating but if needed the density can be adjusted up to 1,20 to ensure that the rope is sinking.

Diameter mm	MBL ton	Weight in sea kg	Weight kg/m
12	12	-0.009	0.11
14	18	-0.011	0.141
16	25	-0.015	0.184
18	31	-0.018	0.219
20	39	-0.024	0.295
22	44	-0.026	0.318
24	47	-0.031	0.384
26	56	-0.035	0.439
28	65	-0.042	0.523
30	74	-0.046	0.576
32	83	-0.053	0.662
34	91	-0.057	0.71
36	99	-0.065	0.804
38	107	-0.069	0.863
40	115	-0.073	0.915
42	134	-0.079	0.979
44	142	-0.084	1.043
46	146	-0.093	1.155
48	157	-0.099	1.229
50	169	-0.105	1.311