

## Wire Rope Clamp BG



### Product information

**General:** Wire rope clamp type, approved for lifting. Requires fewer clamps per fixation, e.g. two wire clamps instead of four, for 16 mm cable. Symmetrical – cannot be wrongly fitted. The clamps ensure fixation of the wire to a degree of at least 90% of the minimum breaking load of the wire in accordance with the current European standard.

**Design:** Bases of cast steel.

**Finish:** Body Hot dip galvanized and bolt electro galvanized

**Note:** Follow the fitting instructions in the user manual before use. Not for use with compacted or hammered wire ropes.

| Part code   | Rope Ø range mm | Thread | No. of clips when lifting | Torque Nm | Weight kg/100pc |
|-------------|-----------------|--------|---------------------------|-----------|-----------------|
| 10.17BG0600 | 5-6             | M6     | 2                         | 9,5       | 9               |
| 10.17BG0800 | 6.5-8           | M6     | 2                         | 9,5       | 12              |
| 10.17BG1000 | 8.5-10          | M8     | 2                         | 22        | 20              |
| 10.17BG1200 | 11-12.5         | M10    | 2                         | 44        | 39              |
| 10.17BG1600 | 13-16           | M12    | 2                         | 75        | 72              |
| 10.17BG2000 | 17-20           | M14    | 2                         | 120       | 120             |
| 10.17BG2500 | 21-25           | M18    | 2                         | 260       | 280             |
| 10.17BG3400 | 26-34           | M20    | 2                         | 350       | 770             |