

Female Double Swivel Shackle Codipro SS FE DSS



Product information

Stainless steel female double swivel shackle SS FE DSS.

Design: Centered lifting ring with double articulation except for the SEB, swivel eyebolt 360°.

Material: AISI 316 L

Marking: According to standard, CE-marked, The compliance to EC directives, GRADUP steel quality, The recommended tightening torque, The manufacturer brand, Traceability marks of each component (Blacksmith + batch number), The thread

Temperature range: -20°C up to + 200°C

Finish: An anti-corrosion coating on the unpainted parts of the CODIPRO swivel lifting points and orange color (RAL 2002) for the schackle.

Standard: EN 1677-1

except grade/WLL

Safety factor: 5:1

Part code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D, mm	E mm	F mm	G, mm	L max. mm mm	S mm	Weight kg
11.39SS.FE.DSS M 24	2.7	M 24 (x3)	160	66	31	70	98	73	149	30	66	50	5.8
11.39SS.FE.DSS M 30	3.5	M 30 (x3.5)	250	66	31	70	98	73	149	30	66	50	5.8
11.39SS.FE.DSS M 33	3.5	M 33 (x3.5)	250	66	31	70	98	73	149	30	66	50	5.8
11.39SS.FE.DSS M 36	5	M 36 (x4)	320	66	31	70	98	73	149	30	66	50	5.8

Technical data

5:1

max. load in t	METRIC THREADS													
	Torque (Nm)		1	2	1	2	2			3 → 4				
	Number of rings		1	2	1	2	0° → 45°	45° → 60°	Asymmetric	0° → 45°	45° → 60°	Asymmetric		
	Lifting angle β		0°	0°	0°	0°	0° → 45°	45° → 60°	Asymmetric	0° → 45°	45° → 60°	Asymmetric		
			0°	0°	90°	90°	0° → 45°	45° → 60°		0° → 45°	45° → 60°			
		160	2,70	5,40	2,70	5,40	3,78	2,70	2,70	5,67	4,05	2,70		
		250	3,50	7,00	3,50	7,00	4,90	3,50	3,50	7,35	5,25	3,50		
		250	3,50	7,00	3,50	7,00	4,90	3,50	3,50	7,35	5,25	3,50		
		320	5,00	10,00	5,00	10,00	7,00	5,00	5,00	10,50	7,50	5,00		
		320	5,00	10,00	5,00	10,00	7,00	5,00	5,00	10,50	7,50	5,00		
		320	5,00	10,00	5,00	10,00	7,00	5,00	5,00	10,50	7,50	5,00		
		400	6,00	12,00	6,00	12,00	8,40	6,00	6,00	12,60	9,00	6,00		
		400	6,00	12,00	6,00	12,00	8,40	6,00	6,00	12,60	9,00	6,00		

Blueprint

