

Swivel Eye Bolt Codipro SEB UP

Product information



The SEB lifting ring is a single swivel ring. Equipped with 2 pins that always guide it perfectly in the direction of the sling. It is specially designed for lifting, including rotating loads.

Features:

- Gradup steel ring that has a rotating range of 360°.
- Swivelling under load
- Safe alternative to C15 DIN 580 eye bolts.
- Torque key adaptor available on request.

[... Read more](#)

Material: High tensile steel

Marking: According to standard, CE-marked


Temperature range: -20°C up to +200°C

Standard: EN 1677-1
except grade/WLL

Safety factor: 5:1

Swivel Eye Bolt Codipro SEB UP

Blueprint



Technical data

Part code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	L1 mm	S mm	X mm	Weight kg
11.42SEB M 8 UP	0.4	M 8 (x1.25)	6	30	34	60	57	14	6	20	0.24
11.42SEB M 10 UP	0.5	M 10 (x1.50)	10	30	34	60	57	17	6	20	0.24
11.42SEB M 12 UP	0.8	M 12 (x1.75)	15	30	34	60	57	21	6	20	0.24
11.42SEB M 16 UP	1.4	M 16 (x2)	50	38	45	88	80	27	8	35	0.8
11.42SEB M 20 UP	2	M 20 (x2.5)	100	38	45	88	80	30	8	35	0.8
11.42SEB M 24 3T8 UP	3.2	M 24 (x3)	160	38	45	88	80	36	14	35	0.8
11.42SEB M 24 4T2 UP	3.4	M 24 (x3)	160	58	70	115	106	36	14	50	2.6
11.42SEB M 30 UP	5.5	M 30 (x3.5)	250	58	70	115	106	45	14	50	2.7
11.42SEB M 36 UP	9	M 36 (x4)	320	83	94	168	155	54	14	70	7
11.42SEB M 42 UP	12	M 42 (x4,5)	400	83	94	168	155	63	14	70	7
11.42SEB M 48 UP	15	M 48 (x5)	600	80	94	168	155	68	19	70	7