



Double Swivel Lifting Ring Codipro Giga DSS

Product information

The universal swivel shackle GIGA DSS is a double swivel ring. It is specially designed for simultaneously lifting and rotating of very heavy loads. Its double swivel action ensures perfect alignment with the sling.

Features:

- Swiveling under load
- Usable for any kind of heavy lifting operation
- The tightening torque is stamped on all lifting rings in the GRADUP range.

Material: High tensile steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +200°C

Standard: EN 1677-1

except grade/WLL











Safety factor: 5:1

Part code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	L1 mm	S1 mm	S2 mm	Weight kg
11.42GIGA.DSS M 150 UP	125	M 150 (x6)	2,000	271	115	290	353	302	544	103	228	41	105	268

Technical data

5:1

max. load in t

METRIC THREADS		Torque (Nm)										
Number of rings			1	2	1	2	2			3 → 4		
Lifting angle β			0°	0°	0°	0°	0° → 45°	45° → 60°	Asymmetric	0° → 45°	45° → 60°	Asymmetric
Loading angle α			0°	0°	90°	90°	0° → 45°	45° → 60°		0° → 45°	45° → 60°	
MEGA.DSS+ M 64 UP	600		30,00	60,00	30,00	60,00	42,00	30,00	30,00	63,00	45,00	30,00
MEGA.DSS+ M 72 UP	700		35,00	70,00	35,00	70,00	49,00	35,00	35,00	73,50	52,50	35,00
MEGA.DSS+ M 72x4 UP	700		35,00	70,00	35,00	70,00	49,00	35,00	35,00	73,50	52,50	35,00
MEGA.DSS+ M 80 UP	800		40,00	80,00	40,00	80,00	56,00	40,00	40,00	84,00	60,00	40,00
MEGA.DSS+ M 90 UP	900		50,00	100,00	50,00	100,00	70,00	50,00	50,00	105,00	75,00	50,00
MEGA.DSS+ M 100 UP	1000		60,00	120,00	60,00	120,00	84,00	60,00	60,00	126,00	90,00	60,00
GIGA.DSS M 150 UP	2000		125,00	250,00	125,00	250,00	175,00	125,00	125,00	262,50	187,50	125,00
GIGA.DSS+Q M 150 UP	160		125,00	250,00	125,00	250,00	175,00	125,00	125,00	262,50	187,50	125,00

Blueprint

