

## Web Lashing POWERTEX Strong

### Product information

#### POWERTEX

POWERTEX Strong web lashings are available as endless or 2-part lashings and used for exceptional loads.

These web lashings are heavy duty lashing made of high strength polyester yarn and steel ratchets and hooks

Suitable for professional transporters looking for highest strength

- Webbing having min breaking strength of 15000 daN
- Yellow webbing for easy identification
- Both long part and short part carry blue identification tags
- Label gives information on STF and lashing capacity for different lashing connections
- Each part is marked with a unique serial number for safe equipment registration
- The blue information label is protected by additional layer of transparent plastic for long life
- Year/Month calendar printed on the label where latest inspection date can be marked or punched
- All lashings carry a white label with important warning instructions and user instruction pictogram
- Each lashing marked with QR code to access full user manual
- Cr6 free galvanization – better for health and environment
- Strong can be supplied with other lengths and other end fittings on request.

**Safety factor:** Webbing min. 3, Ratchets min. 2 and Hooks min. 2

**Material:** Polyester and steel

**Marking:** According to standard, POWERTEX, LC, STF, length, manufacturing year, batch number, serial number, QR code, inspection calendar, user warning instructions

**Temperature range:** -40°C up to +120°C

**Standard:** EN 12195-2

**Note:** The standard configuration is with double hooks, but it can also be supplied with other end fittings upon request.



Part code	LC daN	2xLC (daN)	Length m	Band width mm	Design	Fitting	STF daN
14.02STR01WD0595YW	5,000	10,000	10	75	2-part	Wire hook double	500