

Chain SA/S - EN818-2 Gr. 10

Product information

General: Chain for lifting or lashing (other safety factor). Available in 2 different qualities

Star Alloy (SA/S)

- Working temperature: max. 200°C
- Grade Marking: "10" on link every 300mm (up to 16mm) others every 900 mm.
- Surface: Purple varnished



Star Alloy Plus+ (SAP/S): for working temperatures up to 380°C (Available on request)

... [Read more](#)

Material: Alloy steel.

Marking: According to standard

Temperature range: Star Alloy SA/S: -40°C up to 200°C - Star Alloy Plus+ SAP/S: -40°C up to 380°C

Standard: EN 818-2

higher capacity


Warning: Not to be heat treated.

Safety factor: 4:1

Grade: 10

Chain SA/S - EN818-2 Gr. 10

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	Min. breaking force kN	Pitch Length	D, mm	Pmm mm	Li min. mm	Le max. mm	Weight kg/m
11.6570261	6	1.4	56.5	18	6	18	8.7	22	0.96
11.6570264	7	1.9	77	21	7	21	9.5	25	1.2
11.6570267	8	2.5	101	24	8	24	10.9	29	1.57
11.6570270	10	4	157	30	10	30	13.5	36	2.46
11.6570273	13	6.7	265	39	13	39	17.5	47	4.18
11.6570275	16	10	402	48	16	48	21.5	58	6.28
11.6570278	19	14	567	57	19	57	26.6	69	8.9
11.6570281	22	19	760	66	22	66	29.5	79	11.88
11.6514160	26	26.5	1,060	78	26	78	35	94	16.18