

## Chain - Short Link Grade 8

---

### Product information

Chain for lifting and also allowed to use in lashing systems according to EN 12195-3.

... [Read more](#)

---



**Material:** Alloy steel.

**Marking:** According to standard

**Finish:** Painted.

**Standard:** EN 818-2

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 8

## Chain - Short Link Grade 8

### Blueprint



### Technical data

Part code	Chain diameter mm	WLL ton	Min. breaking force kN	D mm	E mm	H mm	Weight kg/m
11.648182060P	6	1.12	45.2	6	18	8.5	0.8
11.648182070P	7	1.5	61.6	7	21	10.5	1.1
11.648182080P	8	2	80.4	8	24	11.5	1.4
11.648182100P	10	3.15	126	10	30	14	2.2
11.648182130P	13	5.3	212	13	39	19	3.8
11.648182160P	16	8	322	16	48	23	5.7
11.648182190P	18	10	407	18	54	23.4	7.3
11.648182200P	20	12.5	503	20	60	26	9
11.648182220P	22	15	608	22	66	28,6	11
11.648182260P	26	21.2	849	26	78	33,8	15
11.648182320P	32	31.5	1,290	32	96	41,6	23