

Stainless Rigging Screw with Jaw/Terminal

Product information

Stainless steel rigging screws design: fork / terminal a.k.a jaw / terminal.
Also available with other end fittings on request. The larger size rigging screws from M20 and up are designed with a rounded fork head and are available with Stainless Steel with bronze threaded inserts for smooth adjustment.

... [Read more](#)



Material: Stainless steel AISI 316.

Marking: Thread and/or wire size


Temperature range: -50°C to +100°C and briefly up to +200°C

Finish: Polished.

Warning: It is strongly recommended to lubricate threads first, before tensioning.

Stainless Rigging Screw with Jaw/Terminal

Blueprint



Technical data

Part code	Rope Ø range mm	Pin diameter mm	Size	Packing Qty.	PIN mm	A mm	B mm	D mm	L1 mm	L2 mm	Weight kg/100pc
10.07120205	2	5	M5	10	5	7.5	9.4	5.5	198	144	4.5
10.07120505	2.5	5	M5	10	5	7.5	9.4	5.5	201	147	4.6
10.07120306	3	5	M6	10	5	7.5	9.4	6.35	232	170	8.5
10.07120306X	3	6	M6	10	6	9.5	10.4	6.35	233	171	8.5
10.07120406	4	5	M6	10	5	7.5	10.4	7.5	242	180	8.7
10.07120406X	4	6	M6	10	6	9.5	10.4	7.5	242	180	9.1
10.07120408	4	6	M8	10	6	9.5	10.4	7.5	275	199	13
10.07120408X	4	8	M8	10	8	11	12.2	7.5	277	201	13
10.07120508	5	6	M8	10	6	9.5	13	9	281	205	13.2
10.07120508X	5	8	M8	10	8	11	12.2	9	284	208	14.8
10.07120510	5	8	M10	10	8	11	14	9	312	228	22.5
10.07120510X	5	9.5	M10	10	9.5	12.5	14	9	316	236	22.5
10.07120610	6	8	M10	10	8	11	17	12.6	328	248	25.6
10.07120610X	6	9.5	M10	10	9.5	12	18.5	12.58	330	250	27.4
10.07120612	6	12	M12	5	12	14	14	12.58	393	287	47.5
10.07120712	7	12	M12	5	12	14	25	14.2	401	295	50
10.07120714	7	12	M14	5	12	14	25	14.2	439	319	58
10.07120714X	7	14	M14	5	14	18	32	14.2	453	335	68.8
10.07120812	8	12	M12	5	12	14	25	16	416	310	53.5
10.07120814	8	12	M14	5	12	14	25	16	453	333	63.5
10.07120816	8	14	M16	5	14	18	32	16	498	365	89.5
10.07120816L	8	14	M16	5	14	22	30	16	494	361	89.5

Stainless Rigging Screw with Jaw/Terminal

Technical data

Part code	Rope Ø range mm	Pin diameter mm	Size	Packing Qty.	PIN mm	A mm	B mm	D mm	L1 mm	L2 mm	Weight kg/100pc
10.07120816X	8	16	M16	5	16	17	32.5	16	496	374	89.5
10.07121016	10	14	M16	5	14	18	33	17.8	506	373	93
10.07121016L	10	14	M16	5	14	22	33	17.8	504	371	93
10.07121016X	10	16	M16	5	16	18	33	17.8	510	376	93
10.07121020	10	19	M20	Bulk	19	24	48	17.8	587	427	170.1
10.07121220	12	19	M20	Bulk	19	24	48	20	603	453	170.1
10.07121220X*	12	19	M20	Bulk	19	24	48	21.4	622	462	170.1
10.07121422	14	22	M22	Bulk	22	30	58	25	590	555	452
10.07121424	14	25.4	M24	Bulk	25.4	30	47.8	25	846	613	642
10.07121622	16	22	M22	Bulk	22	30	57.5	28	696	588	490
10.07121624	16	25.4	M24	Bulk	25.4	30	62	28	874	644	662
10.07121927	19	28	M27	Bulk	28	32	68	34.5	968	734	878
10.07122230	22	32	M30	Bulk	32	35	76	40.5	1,076	814	1,074
10.07122636	26	35	M36	Bulk	35	40	86	46	1,195	921	1,682