

## **Lanyard with Shock Absorber, 3M Protecta - Rope Version**

## **Product information**

3M, Protecta rope lanyard rope version with shock absorber, max. user weight 130 kg.

## Connectors:

type: 1260351 and 1260353:

Harness side: Oval steel carabiner - opening 18mm

Anchorpoint side: Self-locking galv. steel scaffold hook(s) - opening 50mm

type: 1260350 and 1260352:

Harness side: Self-locking galv. steel snap hook - opening 19mm

Anchorpoint side: Self-locking galv. steel scaffold hook(s) - opening 50mm

Life expectancy: Max. 10 years from manufacturing date.

## Features:

- 130 kg. Max rating allows a greater range of users.
- Small and compact schock absorber pack.
- Labels fully covered for long term indentification.
- Lightweight. Helps reduce the carry weight of your equipment.
- ø 10.5mm rope for easy and flexible handling.
- Available in single-leg and twin-leg version
- Available with different hooks and karabiners (see product images)

Material: Rope - Carabiners and hooks Steel.

Marking: According to standard, CE-marked

Temperature range: -35°C up to 57°C

Standard: EN 355

Part code	Max. number of persons	Length m	Number of legs	Max. user weight kg	Weight kg
19.04.1260331	1	2	1	130	0.8
19.04.1260334	1	2	1	130	0.8
19.04.1260332	1	1.8	2	130	1.4
19.04.1260333	1	1.8	2	130	1.4