MENNENS | Lifting Solutions Group
Axel Johnson International

Safety Harness ExoFit™ XE50 1112702 / 03 / 04

Product information



he 3M™ DBI-SALA® ExoFit™ XE50 is designed with high-quality components specially developed for enhanced safety and fit while working at heights. Built with durable 26kN polyester webbing and alloy steel hardware, 3M™ DBI-SALA® ExoFit™ XE50 was created to endure the daily conditions of your job site.

The back D-ring plate design with pSRL tunnel allows quick and easy connection of a personal SRL. Revolving torso-adjustment buckles and buckles will help get your team get a quick, safe, and comfortable harness fit. This harness is compatible with optional accessory for back/shoulder padding, leg padding and with variety of 3M fall protection for tools accessories.

All models are equipped with low-profile suspension trauma relief straps.
Attachment point:
• Rear: Large D-ring – Steel - zinc plated
• Front: Standard D-ring– Steel - zinc plated

Buckles:
• Legs: Pass-through– Steel - zinc plated/black paint
• Chest: Pass-through – Steel - zinc plated/black paint

Size adjustment:
• Legs and Torso
• Torso: Revolving adjuster – Steel/aluminium - ratchet buckle

Additional features:
• Front & rear fall indicators
• 2x Auto-resetting/repositionable lanyard keepers
• RFID Equipped
• Dedicated personal self-retracting lifeline attachment point

... *Read more*

Material: Webbing Polyester - D-rings and Buckles" Steel/Aluminium
Marking: According to standard, CE-mark, UKCA-marked
Standard: EN 361


Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Safety Harness ExoFit™ XE50 1112702 / 03 / 04

Blueprint



Technical data

Part code	Size	Max load kg	Weight kg
820100772340	1	140	1.65
820100782340	2	140	1.7
820100792340	3	140	1.75

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved