

Lifting Bag RLB

Product information



Lifting bag RLB for lifting, separating, fixing and pushing.
Given WLL = Max. Capacity at Max. Working pressure 8 bar.

- Side marks for proper installation
- Easy to carry handles
- Better adhesion due to the square form
- Centre sign

Lifting Bags must be used by those persons who are well trained and are able to completely perform the user manual.

Available Accessories:

- Single Controller RLB
- Double Controller RLB
- Line Shut-Off Valve RLB
- Airhose RLB

Marking: CE-marked

Note: Accessories sold separately.

Warning: Don't use 2 or more Lifting Bags on top of each other.

Code	WLL ton	Size	Lifting height m	max.working pressure bar/Mpa	Max. lifting kN	Weight kg
RLB 115	1.17	140 x 140 x 23 mm	0.075	8	11.5	0.4
RLB 350	3.56	200 x 260 x 23 mm	0.1	8	35	1
RLB 620	6.32	300 x 300 x 23 mm	0.17	8	62	2
RLB 1030	10.5	380 x 380 x 23 mm	0.21	8	103	3.8
RLB 1840	18.76	500 x 500 x 23 mm	0.29	8	184	6.4
RLB 2700	27.53	600 x 600 x 25 mm	0.36	8	270	9.8
RLB 3700	37.72	700 x 700 x 25 mm	0.42	8	370	13.5
RLB 4870	49.66	800 x 800 x 25 mm	0.47	8	487	17.8
RLB 6200	63.22	900 x 900 x 25 mm	0.5	8	620	21
RLB 7600	78.31	1000 x 1000 x 25 mm	0.59	8	768	24.5