

GKS-Perfekt Jacks

Product information

Safety is a key feature of the GKS-PERFEKT toe jack. Manufactured to a high safety margin, it includes a release valve that allows loads to be lowered precisely and carefully, plus a safety valve for overload protection. Additionally, the toe jack is built with our well proven, one-piece, height-adjustable safety toe.



| Part code | WLL ton | Type | Stroke mm | Loading height min.-max. mm | Loading height - top plate mm | No. of lifting positions | Working pressure (bar) | A mm | B mm | C mm | D mm | E mm | Weight kg |
|-------------|---------|------|-----------|-----------------------------|-------------------------------|--------------------------|------------------------|------|------|------|------|------|-----------|
| 16.35GKSV5 | 5 | V5 | 140 | 15 - 136 | 252 | 3 | 520 | 285 | 235 | 252 | 15 | 140 | 21.6 |
| 16.35GKSV10 | 10 | V10 | 160 | 20 - 170 | 310 | 4 | 520 | 357 | 260 | 310 | 20 | 160 | 32.4 |
| 16.35GKSV15 | 15 | V15 | 160 | 25 - 175 | 318 | 4 | 520 | 403 | 320 | 318 | 25 | 160 | 52 |
| 16.35GKSV20 | 20 | V20 | 160 | 25 - 160 | 325 | 3 | 520 | 425 | 326 | 325 | 30 | 160 | 70.8 |

Blueprint

