

Fall Arrest Block IKAR HWPB with Webbing

Product information



Robust, low-maintenance fall arrest device with webbing and swivel. The swivel prevents the webbing from twisting. Internal energy-absorber and hook with fall indicator.

Low weight thanks to extra light plastic housing.

Approved for vertical and horizontal use.

Edge tested: Tested at sharp edges, $R \geq 0,5$ mm (CNB/P/11.060 2008 sharp edge Type A)

Carabiner: IKAR Small swivel snap hook IKV11 ($L_k = 136,5$ mm -opening $\varnothing 25$ mm).

The blocks can also be delivered with the following approvals: ANSI/ASSE Z 359.14-2014/LE up on request.

[... Read more](#)

Material: Body: plastic, webbing: Dyneema®

Marking: According to standard, CE-marked

Temperature range: -40°C to +50°C.

Standard: EN 360

Fall Arrest Block IKAR HWPB with Webbing

Blueprint



Technical data

Part code	Code	Max. number of persons	Length m	Max load kg	Dimensions mm	L mm	B mm	T mm	Lk mm	Lk mm	Lk mm	Weight kg
19.0741-HWPB12	HWPB 12	1	12	136	370 x 195 x 95	370	195	95	136.5	-	-	3.4
19.0741-HWPB15	HWPB 15	1	15	136	400 x 195 x 95	400	195	95	-	136.5	-	4.8
19.0741-HWPB3,5	HWPB 3.5	1	3.5	136	326 x 104 x 78	326	104	78	-	136.5	-	1.2
19.0741-HWPB5,5	HWPB 5.5	1	5.5	136	300 x 130 x 78	300	130	78	-	-	136.5	1.5
19.0741-HWPB7	HWPB 7	1	7	136	300 x 165 x 80	300	165	80	-	-	136.5	1.8
19.0741-HWPB9	HWPB 9	1	9	136	335 x 168 x 88	355	168	88	-	-	136.5	2.3