



## Bow Shackle Powertex PBSP

### Product information

#### **POWERTEX**

The POWERTEX Bow Shackle PBSP is a Grade 6 lifting shackle designed for demanding industrial environments where flexibility and efficiency are important. It is supplied with an alloy steel screw pin, allowing quick and easy assembly and disassembly.

The bow shape supports multi-directional loading, making it suitable for use with lifting slings, chains, and wire rope assemblies. Manufactured from quenched and tempered alloy steel and hot dip galvanized, it delivers reliable performance in daily lifting operations.

The PBSP complies with EN 13889, AS 2741 (generally), ASME B30.26 and meets the performance requirements of US Fed. Spec. RR-C-271 Type IVA Class 2 Grade A, supporting safe and compliant lifting across international projects.

#### **When to choose this product:**

Choose the PBSP screw pin version when:

- Speed and ease of handling are important
- The shackle is part of temporary or frequently changed lifting setups
- You need clear marking and traceability for inspection routines

#### **Product benefits:**

- **Screw pin for quick and easy opening**  
Allows fast installation and removal, helping reduce downtime in lifting setups that change frequently.
- **Forged alloy steel, quenched and tempered, Grade 6**  
Provides consistent strength and predictable performance in demanding lifting operations.
- **Safety factor 6:1**  
Designed with a clear safety margin for overhead lifting applications.
- **Hot dip galvanized finish on body and screw pin**  
Protects against corrosion and extends service life in outdoor and industrial environments.
- **Batch marked body and screw pin with full CE and WLL marking**  
Simplifies inspection, traceability, and documentation, helping prevent misuse and overloading.
- **Wide operating temperature range from -40°C up to +200°C**  
Suitable for both cold outdoor sites and warm industrial conditions, without requiring any equipment changes.
- **Compliant with EN 13889, AS 2741, ASME B30.26 and meets US Fed. Spec. RR-C-271 performance requirements**  
Supports safe use in regulated environments and simplifies approval in international projects.
- **Multilingual user manuals in 13 languages**  
Supports correct installation, inspection, and safe use across international teams, helping reduce training errors and ensuring

compliance with local safety procedures.

**Material:** Forged alloy steel, supplied with alloy screw pin.

**Marking:** According to standard, CE-marked, Powertex (PT or PTEX) , WLL, size, grade and batch number.

**Temperature range:** -40°C up to +200°C

**Finish:** All parts hot dip galvanized. Bolt additional powder painted.

**Standard:** EN 13889, AS 2741, ASME B30.26

**Safety factor:** 6:1

**Grade:** 6

Part code	WLL ton	Size inch	a* mm mm	c* mm mm	dmm mm	d1 mm mm	d2 mm mm	e mm mm	H1mm mm	Weight kg
11.31PBSP00033	0.33	3/16	10	22.6	5	6.3	14.5	15.5	29	0.026
11.31PBSP00050	0.5	1/4	13	29	6.5	8	17.5	20	38	0.048
11.31PBSP00075	0.75	5/16	13.5	31	8	9.5	21	21.5	42.5	0.082
11.31PBSP00100	1	3/8	17	36.5	10	11.2	25	26.2	51.5	0.15
11.31PBSP00150	1.5	7/16	18.5	42.9	11.3	12.7	27	29.5	58	0.2
11.31PBSP00200	2	1/2	20.6	47.75	12.7	15.8	30.5	33.3	67	0.3
11.31PBSP00325	3.25	5/8	27	60	16	18.6	40	43	85	0.65
11.31PBSP00475	4.75	3/4	32	71.5	19	22	48	51	98.5	1.01
11.31PBSP00650	6.5	7/8	37	84.5	22	25	54	58	114	1.5
11.31PBSP00850	8.5	1	43.5	96.25	26.5	28	60	68.5	129.5	2.25
11.31PBSP00950	9.5	1-1/8	48	109	29	32	68	75	144	3.25
11.31PBSP01200	12	1-1/4	53	120.5	32	35	76	84	157	4.45
11.31PBSP01350	13.5	1-3/8	59	134	35	38	84	94	171	5.95
11.31PBSP01700	17	1-1/2	62	148.5	38	42	92	99	186	7.72
11.31PBSP02500	25	1-3/4	75	178	45	50	106	128	227	12.64
11.31PBSP03500	35	2	84	197.5	52	55	122	148	253	18.72
11.31PBSP05500	55	2-1/2	107	269.5	66	70	145	186	318	37

# Blueprint

