

Spur Gear Hand Winch TL150 Painted

Product information



This small compact hand-operated winch weighing only 4 kg excels because of its high speed. Its speed and size make it well suited to smaller jobs.

- robust and safe winch suitable for lifting and pulling
- Load pressure brake with double ratchet system for safe stable hold of the load in any position
- wire rope outlet upwards
- adjustable crank
- suitable for wall mounting
- 1 layer of paint

Options:

- zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- ATEX certified zone 2 and 22 (EX)
- CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +70°C

Finish: Painted, grey


Standard: EN 13157

Note: The cable must be ordered separately, ask for more information about our sales

Safety factor: 4:1

Spur Gear Hand Winch TL150 Painted

Blueprint



Technical data

| Code | WLL ton | Rope Ø mm | Rope capacity m | Capacity 1st layer kg | Capacity top layer kg | Weight kg |
|-------|---------|-----------|-----------------|-----------------------|-----------------------|-----------|
| TL150 | 0.15 | 4 | 13.1 | 150 | 67 | 4 |