

## Lifting Arm NEO HV

### Product information



The Neo HV lifting arm, in connection with a Neo lifting magnet, is a versatile aid for handling loads from the horizontal to the vertical position and vice versa. For example, if a plate is on a pallet and you need to move it to a lathe, you must usually make use chains, clamps, and at least two workers. With a lifting arm equipped with a Neo permanent lifting magnet, you will save manpower and make the operation more efficient.

#### Features:

- Possibility to adjust the arm to a wide range of diameters and widths
- Removable lifting arm for magnet replacement
- Robust lifting eye

**Marking:** According to standard

**Temperature range:** Up to +80°C

**Finish:** Painted.

**Standard:** EN 13155

**Note:** Only suitable for NEO and NEO HOT, which have to be ordered separately.

**Safety factor:** 3:1

| Part code          | Code     | WLL<br>ton | Width<br>mm | W<br>mm | L<br>mm | H<br>mm | Weight<br>kg |
|--------------------|----------|------------|-------------|---------|---------|---------|--------------|
| 16.45LH30PENOV7253 | LARM250  | 0.25       | 300-800     | 210     | 958     | 244     | 16           |
| 16.45LH30PENOD3891 | LARM500  | 0.5        | 300-1,000   | 210     | 1,158   | 244     | 20           |
| 16.45LH30PENOP7261 | LARM1000 | 1          | 300-1,000   | 210     | 1,211   | 297     | 33           |

Blueprint

